

Electrically Conductive Epoxy Flake Floor Coating For Static - Sensitive Industries MSDS

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 300KG
- Price: US\$4.0-6.0/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year

CREKOAT



Product Specification

- Goods Nameplate: Flake Epoxy Coating
- Principal Attribute: Low Viscosity
- Key Words: Self-Leveling, Fast Curing
- Materials: Epoxy With Flakes
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Electrically Conductive Epoxy Flake Floor Coating**
, MSDS Epoxy Flake Floor Coating

CREKOAT



Product Description

Electrically Conductive Epoxy Flake Floor Coating For Static-Sensitive Industries

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coating seamlessly unites durability and artistry. It's incredibly robust, standing up to high traffic and daily wear, ensuring a lasting investment. Its chemical resistance makes it an ideal choice for areas prone to spills. What truly distinguishes it is the creative canvas it offers, with a wide spectrum of colors and flake patterns that transform spaces into unique expressions of personal style. Maintenance is simple with its easy-to-clean seamless surface. Versatile and suitable for various settings, from garages to showrooms, it offers both function and style. The coating's slip-resistant properties enhance safety, while its impermeable, seamless finish keeps moisture at bay. Epoxy flake floor coating isn't just flooring; it's a statement of durability and artistry.

Features Of Epoxy Flake Floor Coating:

1. Prevents bacterial colonization
2. Suitable for static-sensitive industries
3. Strong adhesion for lasting protection
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa.s	50-150 mPa.s
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China