

Aromatic Resin Epoxy Flake Floor Coating Customize Fast Curing

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 300KG

• Price: US\$4.0-6.0/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

Supply Ability: 1000000 Ton/Year



Product Specification

Line Brand Emblem: Epoxy Resin FlakesIndicative Quality: Tough Elasticity

• Key Words: Self-Leveling, Fast Curing

Materials: Epoxy With Flakes

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Aromatic Resin Epoxy Flake Floor Coating,

Fast Curing Epoxy Flake Floor Coating

Product Description

Aromatic Resin Epoxy Flake Floor Coating Offers Various Choices For Customize

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coating reimagines flooring as an art form, blending durability and aesthetics. Its robustness is unmatched, enduring high traffic and chemical exposure with ease. What sets it apart is its creative versatility. A vast palette of colors and flake patterns allows for unique, personalized designs, turning any space into a work of art. Be it in residential garages, homes, or commercial settings, it marries function and visual appeal. Maintenance is effortless with its easy-to-clean, seamless surface. Its slip-resistant properties ensure safety, and its impermeable, seamless finish keeps moisture at bay. Epoxy flake floor coating isn't just flooring; it's a canvas for resilience and creative expression, ushering in a new era where every step taken is a testament to both durability and style.

Features Of Epoxy Flake Floor Coating:

- 1. Designed for use in submerged environments
- 2. Various aromatic resin choices for customization
- 3. Strong adhesion for lasting protection
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy Flake Coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 mPa⋅s	50-150 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D82-85	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China