

Non-Yellowing Polyaspartic Flooring Maintains Clarity Over Time Without Yellowing

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Carton/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year


CREKOAT



Product Specification

- Product Identifier Emblem: Metallic Polyaspartic Floor Coating
- Critical Characteristic: High Clarity
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Clarity Over Time Polyaspartic Flooring, Clarity Polyaspartic Flooring, Non Yellowing Polyaspartic Flooring**

CREKOAT



Product Description

Non-Yellowing Polyaspartic Flooring Maintains Clarity Over Time Without Yellowing

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings provide a significant advantage over traditional epoxy coatings through their enhanced scratch resistance, ensuring the flooring maintains its appearance despite heavy usage. They also offer superior breathability, reducing the risk of moisture-related issues such as bubbling or delamination. Their ability to cure at very low temperatures allows for year-round application, even in unheated spaces. Furthermore, polyaspartic coatings can be applied in a wide range of thicknesses, accommodating various flooring requirements from thin decorative layers to thick, protective coatings. These properties make polyaspartic coatings a versatile and reliable option for diverse flooring needs.

Features Of Polyaspartic Floor Coating:

1. Made with environmentally friendly components
2. Provides a smooth and even surface upon application
3. Maintains clarity and appearance without yellowing
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China