

Scratch Resistance Garage Floor Coating Polyaspartic Fast Turnaround Within Hours

Basic Information

Place of Origin: DONGGUAN, CHINA

Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 500KG

• Price: US\$8.5-12.5/Kg

Packaging Details: Bottle/Carton/Wooden Box

• Delivery Time: 3-7 Working Days

Payment Terms: T/T, Western Union, MoneyGram

• Supply Ability: 1000000 Ton/Year



Product Specification

• Merchandise Classification Polyaspartic Pool Coating

Symbol:

Major Element: Odorless Setting

Key Words: Interior And Exterior Use
Materials: 90% Solid Polyaspartic
Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Polyaspartic Garage Floor Coating,

Fast Turnaround Garage Floor Coating, Scratch Resistance Garage Floor Coating



Product Description

Scratch Resistance Garage Floor Coating Polyaspartic Fast Turnaround Within Hours

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings offer significant advantages over traditional epoxy coatings. They cure rapidly, reducing downtime and allowing for faster project completion. They are also more UV stable, preventing yellowing and degradation over time. Polyaspartics can be applied in a broader range of temperatures, including very cold conditions, and have superior flexibility, reducing the risk of cracking. They handle moisture better during application, preventing bubbling and adhesion issues, and provide excellent abrasion and chemical resistance, making them ideal for high-traffic and industrial environments.

Features Of Polyaspartic Floor Coating:

- 1. Fast turnaround, back in use within hours of application
- 2. Provides a surface that resists scratches from daily use
- 3. Maintains clarity and appearance without yellowing
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China