



## Food Safe Polyurea Polyaspartic Clear Topcoat Options For Added Protection And Shine

### Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

#### Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year

CREKOAT



#### Product Specification

- Line Identity Marker: General Polymers Polyaspartic
- Eminent Quality: Smooth Finish
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Polyaspartic Topcoat,  
Food Safe Polyaspartic Topcoat,  
Polyurea Polyaspartic Topcoat

CREKOAT



## Product Description

### Food Safe Polyurea Polyaspartic Clear Topcoat Options For Added Protection And Shine

#### Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings offer unique benefits over traditional epoxy coatings, particularly in their resilience and maintenance properties. They are highly resistant to staining and chemicals, making them ideal for environments prone to spills and exposure to harsh substances. The non-porous nature of polyaspartic coatings ensures that dirt and grime do not penetrate the surface, facilitating easier cleaning and maintenance. Additionally, they exhibit superior thermal stability, maintaining their integrity and performance under varying temperature conditions. These attributes make polyaspartic coatings an excellent choice for facilities that require both durability and ease of upkeep, such as laboratories, kitchens, and healthcare settings.

#### Features Of Polyaspartic Floor Coating:

1. Available with clear topcoats for added protection and shine
2. Meets standards for use in food preparation and processing areas
3. Maintains clarity and appearance without yellowing
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

#### Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

#### Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China