



Easy Recoating Epoxy And Polyaspartic Garage Floor Suitable For Basements

Our Product Introduction

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



Product Specification

- Product Emblem Tag: Polyaspartic Polyurea Floor Coating
- Noticeable Mark: High Temperature
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Basements Garage Floor,
Easy Recoating Garage Floor,
Polyaspartic Garage Floor



Product Description

Easy Recoating Epoxy And Polyaspartic Garage Floor Suitable For Basements

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings stand out for their remarkable UV stability and enduring color retention, making them an excellent choice for both outdoor and indoor applications exposed to sunlight. They are formulated to resist yellowing and discoloration, maintaining their vibrant appearance even after prolonged exposure to UV rays. This makes them ideal for surfaces like decks, pool areas, and outdoor furniture, where consistent aesthetic quality is important. Additionally, polyaspartic coatings offer excellent resistance to chalking and surface degradation caused by UV exposure, which helps to maintain their smooth finish and protective properties over time. These attributes ensure that polyaspartic coatings not only look good for longer but also provide lasting protection and performance.

Features Of Polyaspartic Floor Coating:

1. Suitable for basements and below-grade applications
2. Can be easily recoated, simplifying future maintenance
3. Maintains clarity and appearance without yellowing
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China