



Low Temperature Flexibility Polyaspartic Floor Coating High Coverage Rates

Our Product Introduction

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year

CREKOAT



Product Specification

- Product Name Crest: Garage Polyaspartic
- Hallmark Characteristic: Quick Drying
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **High Coverage Rates Polyaspartic Floor Coating**
, Flexibility Polyaspartic Floor Coating,
Low Temperature Polyaspartic Floor Coating

CREKOAT



for more products please visit us on epoxyresinfloorcoating.com

Product Description

Low Temperature Flexibility Polyaspartic Floor Coating High Coverage Rates

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings have several differentiating features that make them stand out. They offer rapid application and quick return-to-service times, hardening within hours and allowing for light use the same day. Compared to epoxy, which takes longer to cure, polyaspartic coatings provide full functionality within 24 hours. They can also be applied in a wide range of temperatures, offering flexibility that other coatings like polyurethane cannot match. Additionally, polyaspartic coatings have excellent UV resistance, chemical resistance, adhesion properties, and customizable aesthetics. They are an optimal choice for projects requiring fast application and durability in commercial and industrial environments.

Features Of Polyaspartic Floor Coating:

1. Maintains flexibility in cold temperatures, reducing the risk of cracking
2. Provides excellent coverage, reducing material costs
3. Maintains clarity and appearance without yellowing
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	



 +8615017402317  info@crekoat.com  epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China