

## High Gloss Retention Polyaspartic Floor Coating UV Stability For Outdoor Applications

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Wooden Box
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 1000000 Ton/Year



### Product Specification

- Branding Stamp: Polyaspartic Coating Garage Floor
- Special Aspect: Strong Adhesion
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **High Gloss Polyaspartic Floor Coating, Outdoor Polyaspartic Floor Coating, UV Stability Polyaspartic Floor Coating**



## Product Description

### High Gloss Retention Polyaspartic Floor Coating UV Stability Ideal For Outdoor Applications

#### Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings differentiate themselves with their exceptional adhesion properties. They form a strong bond with various surfaces, including concrete, steel, and even existing coatings. This superior adhesion ensures long-lasting performance and durability. Additionally, polyaspartic coatings excel in their resistance to extreme temperatures. They can be applied in both hot and cold environments, providing flexibility that other coatings lack. This makes them ideal for projects where temperature variations are common. Moreover, polyaspartic coatings offer a rapid return-to-service time, allowing for quick project completion and reduced downtime. Their fast curing enables light use within hours, minimizing disruptions in commercial and industrial settings. In summary, the exceptional adhesion, temperature resistance, and rapid return-to-service time make polyaspartic coatings a standout choice for demanding projects.

#### Features Of Polyaspartic Floor Coating:

1. Retains its high-gloss finish even under heavy use
2. Resists fading and discoloration from UV exposure
3. Maintains clarity and appearance without yellowing
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

#### Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

#### Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	30-40mins@25°C	
Curing Time	8-12hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China