

Quick Install Epoxy Resin Washed Stone Sound Absorption For Noise Reduction

Basic Information

Place of Origin: DONGGUAN, CHINA

Brand Name: CREKOAT
 Certification: TDS, MSDS
 Model Number: CK-JS1001
 Minimum Order Quantity: 500KG

Price: US\$2.5-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month

CREKOAT

Product Specification

• Signature: Epoxy Natural Stone Flooring

Unique Selling Point: Impact Resistant
 Key Words: UV Resistant
 Materials: Water Based Epoxy
 Application: Wood, Tile, Concrete
 Mixing Ratio: 1:1 By Weight

Pot Life: 40 Minutes
Shelf Life: 12 Months

• Highlight: Sound Absorption Epoxy Resin Washed Stone,

Noise Reduction Epoxy Resin Washed Stone, Quick Install Epoxy Resin Washed Stone



Product Description

Quick Install Epoxy Resin Washed Stone Sound Absorption For Noise Reduction

Quick Details Of Pebble Stone Epoxy:

Pebble stone epoxy flooring is a decorative flooring system that incorporates small pebbles or stones within an epoxy resin to create a visually appealing and durable surface. This flooring solution blends the natural beauty of pebbles with the strength and resilience of epoxy, offering a unique aesthetic that can be customized with various colors and patterns. Pebble stone epoxy floors are known for their durability, low maintenance requirements, slip-resistant properties, and the ability to withstand heavy foot traffic, making them suitable for both residential and commercial spaces. The installation process involves embedding the pebbles in the epoxy resin and sealing the surface for a polished finish.

Features Of Pebble Stone Epoxy:

- 1. Sound absorption for noise reduction
- 2. Magnetic pebbles for custom designs
- 3. Natural and visually appealing texture
- 4. Easy to clean and maintain
- 5. Resistant to stains and chemicals
- 6. Wide range of color options available

Advantages Of Pebble Stone Epoxy:

Pebble stone epoxy flooring offers a visually appealing and durable solution for residential and commercial spaces, combining aesthetic charm with strength. Its slip-resistant texture, low maintenance requirements, customization options, versatility for indoor and outdoor use, and resistance to chemicals make it a popular choice. With its unique blend of natural stones and epoxy resin, pebble stone epoxy provides a long-lasting, safe, and customizable flooring option suitable for a variety of applications.

Product Descriptions Of Pebble Stone Epoxy:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D85-90	
Pot Life	30-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	3-5 mm / 5-10mm	
Shelf Life	12 Months	
Application	Ideal for driveways, pathways, patios, and pool surrounds. In commercial	
	settings, it's used for car parks, shopping centers, and public spaces. It's also	
	popular in landscaping, tree pits, and decorative borders. Its permeability suits	
	sustainable urban drainage systems (SUDS), effectively managing surface	
	water runoff.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China