

UV-Resistant Stone Epoxy Driveway Natural Glow Pebbles For Outdoor Durability

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-JS1001
- Minimum Order Quantity: 500KG
- Price: US\$2.5-4.5/Kg
- Packaging Details: Bottle/Carton/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month

CREKOAT



Product Specification

- Brand Designation: Wood And Stone Epoxy
- Special Highlight: Natural Aesthetics
- Key Words: UV Resistant
- Materials: Water Based Epoxy
- Application: Wood, Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Natural Glow Stone Epoxy,
UV-Resistant Stone Epoxy,
Outdoor Durability Stone Epoxy**

Product Description

UV-Resistant Stone Epoxy Driveway Natural Glow Pebbles For Outdoor Durability

Quick Details Of Pebble Stone Epoxy:

Pebble stone epoxy flooring is typically installed by first preparing the subfloor, mixing the epoxy resin, and then spreading a layer of the resin onto the floor surface. Pebbles or stones are then scattered onto the wet epoxy and troweled into place. After the epoxy cures, the surface is typically sanded down to remove any sharp edges and unevenness, followed by a sealing coat to provide durability and a polished finish.

Features Of Pebble Stone Epoxy:

1. UV-resistant pebbles for outdoor durability
2. Bioluminescent pebbles for a natural glow
3. Natural and visually appealing texture
4. Easy to clean and maintain
5. Resistant to stains and chemicals
6. Wide range of color options available

Advantages Of Pebble Stone Epoxy:

Pebble stone epoxy flooring offers a visually appealing and durable solution for residential and commercial spaces, combining aesthetic charm with strength. Its slip-resistant texture, low maintenance requirements, customization options, versatility for indoor and outdoor use, and resistance to chemicals make it a popular choice. With its unique blend of natural stones and epoxy resin, pebble stone epoxy provides a long-lasting, safe, and customizable flooring option suitable for a variety of applications.

Product Descriptions Of Pebble Stone Epoxy:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D85-90	
Pot Life	30-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	3-5 mm / 5-10mm	
Shelf Life	12 Months	
Application	Ideal for driveways, pathways, patios, and pool surrounds. In commercial settings, it's used for car parks, shopping centers, and public spaces. It's also popular in landscaping, tree pits, and decorative borders. Its permeability suits sustainable urban drainage systems (SUDS), effectively managing surface water runoff.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China