

Anti-Mildew Stone Setting Epoxy For High-Humidity Environments

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-JS1001
- Minimum Order Quantity: 500KG
- Price: US\$2.5-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Goods Tag: White Marble Epoxy Flooring
- Individual Aspect: Enhanced Durability
- Key Words: UV Resistant
- Materials: Water Based Epoxy
- Application: Wood, Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Anti Mildew Stone Setting Epoxy,
High Humidity Stone Setting Epoxy**

Product Description

Anti-Mildew Stone Setting Epoxy For High-Humidity Environments

Quick Details Of Pebble Stone Epoxy:

The installation process of pebble stone epoxy flooring involves meticulous steps to ensure a flawless finish. After prepping the subfloor, a blend of epoxy resin is carefully poured and spread evenly. Next, natural pebbles are delicately placed onto the epoxy, creating a unique pattern or design. The surface is then meticulously troweled to embed the pebbles and achieve a smooth, level finish. Once cured, the floor is polished to reveal the natural beauty of the stones and coated for added durability. This intricate process results in a stunning floor that seamlessly combines artistry with practicality, making each installation a bespoke masterpiece.

Features Of Pebble Stone Epoxy:

1. Anti-mold and mildew properties for high-humidity environments
2. Embedded fiber optics for a starry night effect
3. Natural and visually appealing texture
4. Easy to clean and maintain
5. Resistant to stains and chemicals
6. Wide range of color options available

Advantages Of Pebble Stone Epoxy:

Pebble stone epoxy flooring offers a visually appealing and durable solution for residential and commercial spaces, combining aesthetic charm with strength. Its slip-resistant texture, low maintenance requirements, customization options, versatility for indoor and outdoor use, and resistance to chemicals make it a popular choice. With its unique blend of natural stones and epoxy resin, pebble stone epoxy provides a long-lasting, safe, and customizable flooring option suitable for a variety of applications.

Product Descriptions Of Pebble Stone Epoxy:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D85-90	
Pot Life	30-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	3-5 mm / 5-10mm	
Shelf Life	12 Months	
Application	Ideal for driveways, pathways, patios, and pool surrounds. In commercial settings, it's used for car parks, shopping centers, and public spaces. It's also popular in landscaping, tree pits, and decorative borders. Its permeability suits sustainable urban drainage systems (SUDS), effectively managing surface water runoff.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China