



Natural Pebbles Epoxy Stone Concrete Resurfacing For Contemporary Look

Our Product Introduction

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-JS1001
- Minimum Order Quantity: 500KG
- Price: US\$2.5-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Product Appellation: White Granite Epoxy
- Exclusive Feature: Innovative Textures
- Key Words: UV Resistant
- Materials: Water Based Epoxy
- Application: Wood, Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Natural Pebbles Epoxy Stone Resurfacing ,
Concrete Resurfacing Epoxy Stone**

Product Description

Natural Pebbles Epoxy Stone Concrete Resurfacing For A Contemporary Look

Quick Details Of Pebble Stone Epoxy:

Installing pebble stone epoxy flooring requires a meticulous approach that merges artistry with precision. Beginning with subfloor preparation, a specialized epoxy resin blend is expertly applied and leveled. Natural pebbles are then carefully arranged within the resin, creating a bespoke design tailored to the space. Skilled troweling ensures the pebbles are embedded securely, resulting in a smooth, durable finish. Post-curing, the surface is polished to reveal the stones' natural beauty and sealed for long-lasting protection. This detailed process fuses craftsmanship with durability, culminating in a visually striking floor that harmonizes organic elements with contemporary functionality.

Features Of Pebble Stone Epoxy:

1. Fragrant-infused pebbles for aromatherapy benefits
2. Reflective metallic pebbles for a contemporary look
3. Natural and visually appealing texture
4. Easy to clean and maintain
5. Resistant to stains and chemicals
6. Wide range of color options available

Advantages Of Pebble Stone Epoxy:

Pebble stone epoxy flooring offers a visually appealing and durable solution for residential and commercial spaces, combining aesthetic charm with strength. Its slip-resistant texture, low maintenance requirements, customization options, versatility for indoor and outdoor use, and resistance to chemicals make it a popular choice. With its unique blend of natural stones and epoxy resin, pebble stone epoxy provides a long-lasting, safe, and customizable flooring option suitable for a variety of applications.

Product Descriptions Of Pebble Stone Epoxy:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D85-90	
Pot Life	30-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	3-5 mm / 5-10mm	
Shelf Life	12 Months	
Application	Ideal for driveways, pathways, patios, and pool surrounds. In commercial settings, it's used for car parks, shopping centers, and public spaces. It's also popular in landscaping, tree pits, and decorative borders. Its permeability suits sustainable urban drainage systems (SUDS), effectively managing surface water runoff.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China