

Unique Patterns 2 Part Epoxy For Granite Producing A Unique Floor

Our Product Introduction

Basic Information

- Place of Origin: DONGGUAN, CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-JS1001
- Minimum Order Quantity: 500KG
- Price: US\$2.5-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Line Designation: Stone Flooring For Garages
- Unconventional Aspect: Unique Patterns
- Key Words: UV Resistant
- Materials: Water Based Epoxy
- Application: Wood, Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **2 Part Epoxy, Granite Producing Epoxy, Unique Patterns Epoxy**

Product Description

Unique Patterns 2 Part Epoxy For Granite Producing A Unique Floor

Quick Details Of Pebble Stone Epoxy:

The installation of pebble stone epoxy flooring is a meticulous art form that combines precision with creativity. Starting with thorough subfloor preparation, a specialized epoxy resin blend is applied and leveled to create a smooth foundation. Natural pebbles are then carefully arranged within the resin, allowing for endless design possibilities and personalized patterns. Expert troweling ensures the pebbles are securely embedded, resulting in a durable and aesthetically pleasing surface. After curing, the floor is polished to highlight the natural beauty of the stones and sealed for long-lasting protection. This detailed installation process harmonizes artistic flair with functional durability, producing a unique floor that seamlessly integrates organic elements with modern style and longevity.

Features Of Pebble Stone Epoxy:

1. Thermo-chromatic pebbles for temperature cues
2. Anti-static properties for electronic equipment protection
3. Natural and visually appealing texture
4. Easy to clean and maintain
5. Resistant to stains and chemicals
6. Wide range of color options available

Advantages Of Pebble Stone Epoxy:

Pebble stone epoxy flooring offers a visually appealing and durable solution for residential and commercial spaces, combining aesthetic charm with strength. Its slip-resistant texture, low maintenance requirements, customization options, versatility for indoor and outdoor use, and resistance to chemicals make it a popular choice. With its unique blend of natural stones and epoxy resin, pebble stone epoxy provides a long-lasting, safe, and customizable flooring option suitable for a variety of applications.

Product Descriptions Of Pebble Stone Epoxy:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D85-90	
Pot Life	30-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	3-5 mm / 5-10mm	
Shelf Life	12 Months	
Application	Ideal for driveways, pathways, patios, and pool surrounds. In commercial settings, it's used for car parks, shopping centers, and public spaces. It's also popular in landscaping, tree pits, and decorative borders. Its permeability suits sustainable urban drainage systems (SUDS), effectively managing surface water runoff.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China