

# Residential Pearl Metallic Epoxy Protective Sealants Strong Adhesion To Surfaces

## **Basic Information**

Place of Origin: DONGGUAN, CHINA

Brand Name: CREKOAT
 Certification: TDS, MSDS
 Model Number: CK-MTL2001
 Minimum Order Quantity: 500KG

Price: US\$3.2-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



## **Product Specification**

Shelf Life:

Labeling Title: Metallic Color For Epoxy


Singular Quality: Seamless Design
Key Words: High-Gloss Finish
Materials: 100% Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 2:1 By Weight
Pot Life: 40 Minutes

Highlight: Pearl Metallic Epoxy Protective Sealants,
 Strong Adhesion Epoxy Protective Sealants,

12 Months

**Residential Epoxy Protective Sealants** 

### CREKOAT



## **Product Description**

#### Residential Pearl Metallic Epoxy Protective Sealants Strong Adhesion To Surfaces

#### **Quick Details Of Metallic Epoxy Floor Coating:**

The allure of metallic epoxy flooring emanates from its resilient epoxy resin blend, protective sealants, strong adhesion to surfaces, and resistance to chemicals and imperfections. These components converge to establish a durable flooring solution suitable for residential and commercial settings, harmonizing strength with visual charm. Accurate installation and regular maintenance are pivotal in extending the longevity of metallic epoxy floors, providing a dependable option for those looking to integrate lasting endurance with sophisticated aesthetics in their indoor environments.

#### Features Of Metallic Epoxy Floor Coating:

- 1. Metallic flake size variations for different visual textures
- 2. Magnetic properties for interactive and creative spaces
- 3. Customizable colors and patterns
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Decorative marble appearance flooring

#### **Advantages Of Metallic Epoxy Floor Coating:**

Metallic epoxy floor coating is a low yellowing epoxy resin mixed with metallic pigments. Tiny, shimmering pigments are mixed into the epoxy and poured onto the floor or substrate. When these paints are stirred by a brush or roller, they gather, separate, twist and reflect light at different angles. Eventually, the epoxy hardens and the metallic pigments lock into place, giving them a three-dimensional, swirly appearance. Metallic epoxy floor coatings are not only look beautiful, but can meet all your performance needs. They are perfect for living rooms, office, restaurants, galleries and more.

#### **Product Descriptions Of Metallic Epoxy Floor Coating:**

| Item           | Epoxy Resin(A)   | Hardener(B)   |
|----------------|--|---------------|
| Appearance     | Liquid   | Liquid        |
| Color          | Transparent  | Transparent   |
| Viscosity@25°C | 700-900 mPa·s  | 300-500 mPa⋅s |
| Density, g/cm3 | 1.05±0.05  | 0.95±0.03     |
| Mix Ratio      | 2:1 by weight  |               |
| Hardness       | Shore, D80-85  |               |
| Pot Life       | 30-40mins@25°C   |               |
| Curing Time    | 6-8hrs@35°C, 10-15hrs@25°C   |               |
|                | 24hrs, Dry Completely  |               |
| Recoat Time    | 2Hrs   |               |
| Thickness      | 1-3 mm   |               |
| Shelf Life     | 12 Months  |               |
| Application    | Industrial Use - Garages, Warehouses, Airports and hangars. Commercial   |               |
|                | Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,          |               |
|                | Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - |               |
|                | Entrances and hallways, basements, entertainment rooms, bathrooms,       |               |
|                | kitchens and living rooms.   |               |







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China