

Low VOC Epoxy Flake Floor Coating Offer Unique Blend Of Multicolored Flakes

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 500KG
- Price: US\$3.2-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Inventory Title: Orange Epoxy Flakes
- Differentiating Feature: Durable
- Key Words: Self-Leveling, Fast Curing
- Materials: 100% Solids Epoxy With Flakes
- Application: Wood, Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Low VOC Epoxy Flake Floor Coating,
Multicolored Flake Epoxy Flake Floor Coating,
Unique Blend Epoxy Flake Floor Coating**



Product Description

Low VOC Epoxy Flake Floor Coating Offer A Unique Blend Of Multicolored Flakes

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings offer a unique blend of personalized multicolored flakes, superior durability against stains and impacts, enhanced traction with a textured surface, extensive options for color and design customization, UV stability, and a meticulous multi-layer application process. These features collectively set epoxy flake coatings apart as a distinctive choice for resilient and visually appealing flooring solutions across a variety of spaces.

Features Of Epoxy Flake Floor Coating:

1. Provides thermal shock resistance for extreme temperatures
2. Low VOC options for environmentally conscious projects
3. Enhances safety with slip-resistant properties
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

| Item | Epoxy Resin(A) | Hardener(B) |
|----------------------------|---|---------------|
| Appearance | Liquid | Liquid |
| Color | Transparent | Transparent |
| Viscosity@25°C | 700-900 mPa·s | 300-500 mPa·s |
| Density, g/cm ³ | 1.07±0.05 | 0.95±0.03 |
| Mix Ratio | 2:1 by weight | |
| Hardness | Shore, D80-85 | |
| Pot Life | 30-40mins@25°C | |
| Curing Time | 6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely | |
| Recoat Time | 2Hrs | |
| Thickness | 1-3 mm | |
| Shelf Life | 12 Months | |
| Application | Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms. | |





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China