

## Chip Size Flake Floor Coating Epoxy Variability For Unique Texture Patterns

Our Product Introduction

for more products please visit us on [epoxyresinfloorcoating.com](http://epoxyresinfloorcoating.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 500KG
- Price: US\$3.2-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



### Product Specification

- Designation: Flake Epoxy Floor Coating
- Exquisite Element: Non-Yellowing Properties
- Key Words: High Impact Strength
- Materials: 100% Solids Epoxy With Flakes
- Application: Wood, Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Chip Size Epoxy Flake Floor Coating, Texture Patterns Epoxy Flake Floor Coating**



### More Images



## Product Description

### Chip Size Flake Floor Epoxy Variability For Unique Texture Patterns

#### Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings stand out with their personalized multicolored flakes, superior resistance to stains and impacts, textured surface for improved grip, extensive options for color and design customization, UV stability, and a meticulous multi-layer application process. This unique combination positions epoxy flake coatings as a top-tier selection for durable, visually striking, and adaptable flooring solutions that cater to various design preferences and environmental demands, setting a high standard for long-term performance and aesthetic appeal.

#### Features Of Epoxy Flake Floor Coating:

1. Chip size variability for unique texture patterns
2. High chemical resistance against harsh substances
3. Enhances safety with slip-resistant properties
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

#### Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

#### Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa·s	300-500 mPa·s
Density, g/cm <sup>3</sup>	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China