

Customizable Epoxy Decorative Flakes Floor Coating With Non-Slip Additives For Improved Safety

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 500KG

Price: US\$3.2-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Product Name: Resin Flake Flooring
 Bespoke Quality: Scratch-Resistant Surface
 Key Words: High Impact Strength

• Materials: 100% Solids Epoxy With Flakes

Application: Wood, Tile, Concrete

Mixing Ratio: 2:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Epoxy Decorative Flakes Floor Coating,

Customizable Epoxy Decorative Flakes Floor

Coating

, Non-Slip Epoxy Flakes Floor Coating



Product Description

Customizable Epoxy Decorative Flakes With Non-Slip Additives For Improved Safety

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings set themselves apart with their personalized multicolored flakes, outstanding durability against stains and impacts, textured surface for improved traction, a diverse range of options for color and design customization, UV stability, and a meticulous application process that includes multiple layers. This unique amalgamation positions epoxy flake coatings as a top-tier option for long-lasting, visually striking, and adaptable flooring solutions that cater to a variety of design preferences and environmental considerations, establishing a standard of excellence in both performance and aesthetic sophistication.

Features Of Epoxy Flake Floor Coating:

- 1. Non-slip additives for improved safety
- 2. Customizable thickness levels for specific needs
- 3. Enhances safety with slip-resistant properties
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa⋅s	300-500 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China