



Rapid Curing Full Flake Epoxy Floor Coating For Quick Project Completion Seamless Finish

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-FL2001
- Minimum Order Quantity: 500KG
- Price: US\$3.2-4.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month

CREKOAT



Product Specification

- Brand Title: Epoxy Floor Coating With Flakes
- Distinctive Characteristic: Bubble-Free Casting
- Key Words: High Impact Strength
- Materials: 100% Solids Epoxy With Flakes
- Application: Wood, Tile, Concrete
- Mixing Ratio: 2:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Rapid Curing Epoxy Flake Floor Coating,
Seamless Finish Epoxy Flake Floor Coating,
Seamless Finish Epoxy Flake Floor Coating**

CREKOAT



Product Description

Rapid Curing Full Flake Epoxy Floor For Quick Project Completion Seamless Finish

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings distinguish themselves with their customized multicolored flakes, exceptional resistance to stains and impacts, textured surface for enhanced grip, a wide selection of color and design customization choices, UV resistance, and a detailed application process involving multiple layers. This distinctive combination positions epoxy flake coatings as a premier choice for durable, visually appealing, and versatile flooring solutions that accommodate various design preferences and environmental requirements, setting a high standard for both performance and aesthetic refinement.

Features Of Epoxy Flake Floor Coating:

1. Seamless finish with no grout lines
2. Rapid curing options for quick project completion
3. Enhances safety with slip-resistant properties
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa.s	300-500 mPa.s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China