

# **UV Resistance Epoxy Chip Floor Coating Customizable Color And Design**

# **Basic Information**

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-FL2001 • Minimum Order Quantity: 500KG

• Price: US\$3.2-4.5/Kg Packaging Details: Bottle/Carton/Pallet • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



# **Product Specification**

Shelf Life:

. Merchandise Tag: Concrete Epoxy Paint With Flakes

• Specialized Highlight: Food-Safe Certification . Key Words: High Impact Strength

100% Solids Epoxy With Flakes Materials:

· Application: Wood, Tile, Concrete Mixing Ratio: 2:1 By Weight Pot Life: 40 Minutes

12 Months • Highlight: **UV Resistance Epoxy Chip Floor Coating**, **Customizable Color Epoxy Chip Floor Coating** 



# **Product Description**

## UV Resistance Epoxy Chip Floor With Wide Range Of Choices For Color And Design

### **Quick Details Of Epoxy Flake Floor Coating:**

Epoxy flake floor coatings distinguish themselves with their customized multicolored flakes, exceptional durability against stains and impacts, textured surface for enhanced traction, a wide range of choices for color and design personalization, UV resistance, and a detailed application process involving multiple layers. This distinctive combination positions epoxy flake coatings as a premium choice for enduring, visually captivating, and versatile flooring solutions that address a variety of design preferences and environmental requirements, establishing a high standard for both performance and aesthetic sophistication.

## Features Of Epoxy Flake Floor Coating:

- 1. Anti-microbial properties for hygienic environments
- 2. Flake size options for varying texture effects
- 3. Enhances safety with slip-resistant properties
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Epoxy Flake Floor Coating:**

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

### **Product Descriptions Of Epoxy Flake Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa⋅s	300-500 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China