

Low VOC Formulations Nightfall Epoxy Floor For Eco-Friendly Projects Industrial Settings

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-FL2001
Minimum Order Quantity: 500KG

Price: US\$3.2-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Shelf Life:

• Line Designation: Chip Garage Floor

• Rare Distinction: High Resistance To Yellowing

• Key Words: High Impact Strength

• Materials: 100% Solids Epoxy With Flakes

Application: Wood, Tile, Concrete
Mixing Ratio: 2:1 By Weight
Pot Life: 40 Minutes

• Highlight: Eco-Friendly Projects Epoxy Floor,

12 Months

Low VOC Formulations Epoxy Floor, Industrial Settings Epoxy Floor



Product Description

Low VOC Formulations Nightfall Epoxy Floor For Eco-Friendly Projects Industrial Settings

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings set themselves apart with their individualized multicolored flakes, unmatched durability against stains and impacts, textured surfaces for superior traction, a broad spectrum of choices for color and design customization, UV resistance, and a precise application process involving multiple layers. This exceptional fusion positions epoxy flake coatings as a premier selection for enduring, visually captivating, and adaptable flooring solutions that accommodate a wide spectrum of design preferences and environmental requirements, establishing a standard of excellence in both longevity and aesthetic sophistication.

Features Of Epoxy Flake Floor Coating:

- 1. High heat resistance for industrial settings
- 2. Low VOC formulations for eco-friendly projects
- 3. Enhances safety with slip-resistant properties
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa⋅s	300-500 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China