Superior Scratch Resistance Polyaspartic Floor Coating For Heavy-Duty Applications

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 500KG

Price: US\$8.5-12.5/Kg
Packaging Details: Bottle/Carton/Pallet
Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Goods Title: Polyurea Polyaspartic Coatings

Standout Quality: Low Exothermic Heat
 Key Words: Interior And Exterior Use
 Materials: 90% Solid Polyaspartic

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Scratch Resistance Polyaspartic Floor Coating,

Heavy Duty Polyaspartic Floor Coating, Superior Polyaspartic Floor Coating



Product Description

Superior Scratch Resistance Polyaspartic Floor Coating For Heavy-Duty Applications

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings epitomize adaptability, bridging the divide between indoor and outdoor applications with unparalleled versatility. Their exceptional durability, rapid curing properties, and resistance to UV exposure set them apart as a go-to solution for a myriad of surfaces. Whether safeguarding a busy warehouse floor or enhancing the charm of an outdoor patio, polyaspartic coatings excel in providing long-lasting protection and aesthetics tailored to various environments. Their ability to withstand diverse challenges makes them a top choice for projects ranging from commercial spaces to residential settings, ensuring a durable and appealing finish that endures the test of time.

Features Of Polyaspartic Floor Coating:

- 1. Rapid curing process for quick project completion
- 2. Superior scratch and impact resistance for heavy-duty applications
- 3. Excellent abrasion resistance
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China