



Anti-Slip Polyaspartic Floor Coating With Additives For High-Traffic Areas

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Inventory Naming: Polyaspartic Driveway Coating
- Customized Trait: Low Odor
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Anti-Slip Polyaspartic Floor Coating, Additives Polyaspartic Floor Coating, High-Traffic Areas Polyaspartic Floor Coating**



Product Description

Anti-Slip Polyaspartic Floor Coating With Additives For High-Traffic Areas

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings epitomize a transformative versatility that effortlessly straddles the realms of indoor and outdoor applications, offering a distinctive blend of durability, expedited curing processes, and robust UV resistance. From fortifying industrial floors against heavy wear to rejuvenating outdoor spaces like patios and driveways, these coatings shine in delivering enduring protection and aesthetic allure across a wide spectrum of projects. Whether in a bustling commercial environment or under the open sky, polyaspartic coatings excel in providing a resilient finish customized to tackle diverse environmental demands, ensuring a lasting impact and performance in every application scenario.

Features Of Polyaspartic Floor Coating:

1. Anti-slip additives for improved safety in high-traffic areas
2. High chemical resistance against oils, acids, and solvents
3. Excellent abrasion resistance
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm ³	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	



 +8615017402317  info@crekoat.com  epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China