

Rapid Cure Time Polyaspartic Floor Coating Of 1-2 Hours Faster Project Turnaround

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month


CREKOAT



Product Specification

- Labeling Naming: Polyurea Polyaspartic
- Individual Attribute: Abrasion Resistance
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **1-2 Hours Polyaspartic Floor Coating,
1-2 Hours Floor Coating,
Rapid Cure Time Polyaspartic Floor Coating**

CREKOAT



Product Description

Rapid Cure Time Polyaspartic Floor Coating Of 1-2 Hours Faster Project Turnaround

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings epitomize a versatile solution that seamlessly transitions between indoor and outdoor applications, distinguished by their exceptional durability, rapid curing capabilities, and robust UV resistance. Whether fortifying industrial floors against heavy usage or revitalizing outdoor spaces like patios and driveways, these coatings excel in providing long-lasting protection and aesthetic enhancement across a diverse spectrum of projects. From bustling commercial environments to tranquil outdoor settings, polyaspartic coatings offer a resilient finish customized to meet the distinct challenges presented by various surroundings, ensuring enduring performance and visual appeal in every application scenario.

Features Of Polyaspartic Floor Coating:

1. Rapid cure time of typically 1-2 hours for faster project turnaround
2. Exceptional impact resistance, ideal for high-traffic areas or heavy machinery
3. Excellent abrasion resistance
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China