



Self-Leveling Polyaspartic Floor Coating Enhanced Scratch Resistance To Heavy Wear

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Item Naming: Polyaspartic Coating
- Unique Highlight: High Moisture Resistance
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: **Heavy Wear Polyaspartic Floor Coating,
Scratch Resistance Polyaspartic Floor Coating,
Self Leveling Polyaspartic Floor Coating**



Product Description

Self-Leveling Polyaspartic Floor Coating Enhanced Scratch Resistance To Heavy Wear

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings exemplify a versatile solution that seamlessly adapts to both indoor and outdoor settings, distinguished by their exceptional durability, rapid curing capabilities, and robust UV resistance. Whether fortifying industrial floors against heavy wear or revitalizing outdoor spaces like patios and driveways, these coatings excel in providing enduring protection and aesthetic enhancement across a diverse spectrum of projects. From dynamic commercial environments to serene outdoor retreats, polyaspartic coatings offer a resilient finish customized to meet the distinct challenges posed by various surroundings, ensuring lasting performance and visual appeal in every application scenario.

Features Of Polyaspartic Floor Coating:

1. Self-leveling properties for a smooth, seamless finish without trowel marks
2. Enhanced scratch resistance for areas prone to heavy wear and tear
3. Superior gloss retention over time for a lasting aesthetic appeal
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China