Guangdong Crekoat New Materials Co., Ltd.

High Clarity Polyaspartic Polyurea Coating Color Retention For Long-Lasting **Finish**

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-PLS1001 • Minimum Order Quantity: 500KG

• Price: US\$8.5-12.5/Kg Packaging Details: Bottle/Carton/Pallet • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



Product Specification

. Goods Tagline: Polyaspartic Floor Coating Standout Element: Anti-Static Properties Key Words: Interior And Exterior Use 90% Solid Polyaspartic Materials: · Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By Weight Pot Life: 40 Minutes Shelf Life: 12 Months

• Highlight: High Clarity Polyaspartic Polyurea Coating,

Color Retention Polyaspartic Polyurea Coating, Long Lasting Finish Polyaspartic Polyurea

Coating



Product Description

High Clarity Polyaspartic Polyurea Coating Color Retention For A Long-Lasting Finish

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings, renowned for their rapid curing, often suffice with a single coat, yet the decision for multiple coats hinges on factors like product type, substrate condition, and desired protection. While a single coat may be appropriate for many projects, applying additional layers can enhance durability, color vibrancy, and resilience, particularly in high-traffic settings. Adhering to manufacturer instructions ensures optimal performance, tailoring the application to suit specific project needs for maximum effectiveness.

Features Of Polyaspartic Floor Coating:

- 1. Ultra-low odor formulation for minimal disruption during installation
- 2. High clarity and color retention for a vibrant, long-lasting finish
- 3. Superior gloss retention over time for a lasting aesthetic appeal
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

lk	Delivers estic Desig(A)	Lleveleve v (D)
Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China