



Anti-Slip Textures Polyurea Polyaspartic Coating In Various Levels For Added Safety

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-PLS1001
- Minimum Order Quantity: 500KG
- Price: US\$8.5-12.5/Kg
- Packaging Details: Bottle/Cartron/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Article Symbol: Polyaspartic Pool Paint
- Uncommon Aspect: Heat Conductivity
- Key Words: Interior And Exterior Use
- Materials: 90% Solid Polyaspartic
- Application: Wood, Ceramic Tile, Concrete
- Mixing Ratio: 1:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Polyurea Polyaspartic Coating,
Anti-Slip Textures Polyaspartic Coating,
Various Levels Polyaspartic Coating



Product Description

Anti-Slip Textures Polyurea Polyaspartic Coating In Various Levels For Added Safety

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings distinguish themselves through their remarkable ability to often provide ample coverage in a single coat, owing to their rapid curing properties. While a single application may suffice for many projects, the decision to apply multiple coats is influenced by factors such as the product type, surface condition, and desired level of protection. Opting for additional layers can bolster durability, color vibrancy, and resilience, especially in high-traffic environments. Adhering to the manufacturer's instructions ensures optimal performance, tailoring the application to meet the unique needs of each project for maximum polyaspartic coating efficacy.

Features Of Polyaspartic Floor Coating:

1. Heat resistance up to 300°F (149°C) for industrial settings
2. Anti-slip textures available in various levels for added safety
3. Superior gloss retention over time for a lasting aesthetic appeal
4. Easy to apply, clean and maintain
5. Naturally de-foaming with no ripples
6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C 24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China