

# High Gloss Single Component Polyaspartic Mirror-Like Finishes For A **Luxurious Appearance**

## **Basic Information**

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-PLS1001 • Minimum Order Quantity: 500KG

• Price: US\$8.5-12.5/Kg Bottle/Carton/Pallet · Packaging Details: • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



# **Product Specification**

. Labeling Emblem: Metallic Polyaspartic Flooring

. Singular Property: Odorless

. Key Words: Interior And Exterior Use 90% Solid Polyaspartic Materials:

· Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By Weight Pot Life: 40 Minutes Shelf Life: 12 Months

• Highlight: High Gloss Single Component Polyaspartic,

**Luxurious High Gloss Single Component** 

Polyaspartic

# CREKOAT



## **Product Description**

#### High Gloss Single Component Polyaspartic Mirror-Like Finishes For A Luxurious Appearance

#### **Quick Details Of Polyaspartic Floor Coating:**

Polyaspartic coatings are distinguished by their capacity to often deliver ample coverage in a single application, owing to their swift curing properties. While a singular coat may suffice for numerous scenarios, the decision for multiple applications is guided by factors like product formulation, substrate state, and desired objectives. Adding extra layers can enhance longevity, color vibrancy, and resistance, particularly in high-traffic locales. Adhering to manufacturer guidelines ensures peak performance, tailoring the coating process to suit each project's unique specifications for maximum efficacy of the polyaspartic coating.

#### **Features Of Polyaspartic Floor Coating:**

- 1. High gloss and mirror-like finishes for a luxurious appearance
- 2. Resistance to staining from a wide range of chemicals and substances
- 3. Low temperature application for use in colder climates
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

#### **Advantages Of Polyaspartic Floor Coating:**

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

#### **Product Descriptions Of Polyaspartic Floor Coating:**

Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25ºC	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China