Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PLS1001
Minimum Order Quantity: 500KG

Price: US\$8.5-12.5/Kg
Packaging Details: Bottle/Carton/Pallet
Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Brand Naming: Metallic Polyaspartic Floor Coating
 Peculiar Characteristic: Enhanced Scratch Resistance
 Key Words: Interior And Exterior Use

Materials:
 90% Solid Polyaspartic

Application: Wood, Ceramic Tile, Concrete

Mixing Ratio: 1:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Polyaspartic Metallic Floor Coating,

Polyaspartic Metallic Floor Coating With Flakes

CREKOAT



Product Description

Decorative Effects Polyaspartic Metallic Floor With Metallic Pigments Or Flakes

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings are distinguished by their rapid curing, often requiring just a single coat for sufficient coverage. However, the need for multiple coats depends on factors like product composition, surface preparation, and desired protection levels. While a single coat may suffice for many applications, additional layers can enhance durability, color vibrancy, and resistance, particularly in high-traffic environments. Adhering to manufacturer instructions ensures optimal performance, tailoring the application to suit the unique requirements of each project for maximum efficacy of the polyaspartic coating.

Features Of Polyaspartic Floor Coating:

- 1. Customizable decorative effects such as metallic pigments or flakes
- 2. Breathable formulations for use on concrete substrates
- 3. Increased water and moisture resistance for areas prone to spills
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

	5	
Item	Polyaspartic Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	600-800 cps	50-150 cps
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	1:1 by weight	
Hardness	Shore, D75-80	
Pot Life	40-50mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China