Unique Decorative Epoxy And Polyaspartic Coating 3D Effects Or Custom Patterns

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 500KG
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



Product Specification

- Goods Label:
- Noteworthy Highlight:
- Key Words:
- Materials:
- Application:
- Mixing Ratio:
- Pot Life:
- Shelf Life:
- Highlight:

20	lyurea	And	Poly	aspart	ic

Low Viscosity

F

CHINA

CREKOAT

TDS, MSDS

CK-PLS1001

US\$8.5-12.5/Kg Bottle/Carton/Pallet

3-7 Working Days

1000 Ton/Month

- Interior And Exterior Use
- 90% Solid Polyaspartic
- Wood, Ceramic Tile, Concrete
- 1:1 By Weight
- 40 Minutes
- 12 Months
- Epoxy And Polyaspartic Coating, 3D Epoxy And Polyaspartic Coating

CREKOAT



Our Product Introduction

Product Description

Unique Decorative Epoxy And Polyaspartic Coating 3D Effects Or Custom Patterns

Quick Details Of Polyaspartic Floor Coating:

Polyaspartic coatings excel in their rapid curing, often necessitating just one coat for substantial coverage. However, the decision for multiple coats varies based on factors like product composition, surface condition, and desired outcomes. While a single application suffices for many projects, additional layers can enhance durability, color vibrancy, and resilience, especially in high-traffic environments. Adhering to manufacturer guidelines ensures peak performance, tailoring the application to meet the unique requirements of each project for maximum effectiveness of the polyaspartic coating.

Features Of Polyaspartic Floor Coating:

- 1. Unique decorative options like 3D effects or custom patterns
- 2. Improved resistance to chipping and peeling for long-lasting durability
- 3. High tolerance to heavy loads and machinery
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Polyaspartic Floor Coating:

Polyaspartic flooring offers many advantages over other flooring systems. Its fast-curing properties make it possible to install and finish a floor in as little as one day, reducing downtime and improving productivity. It is highly durable and resistant to abrasion, chemicals, and UV rays, making it a long-lasting and low-maintenance flooring solution. Polyaspartic flooring can be customized with a variety of colors, patterns, and textures, providing endless design possibilities. It is also slip-resistant, improving safety in workplaces and homes. This flooring system is suitable for a variety of applications, including garages, showrooms, hospitals, schools, and even airplane hangars. With its combination of speed, durability, customization options, and low-maintenance features, polyaspartic flooring is a practical and stylish choice for both commercial and residential applications.

Product Descriptions Of Polyaspartic Floor Coating:

Item	Polyaspartic Resin(A)	Hardener(B)		
Appearance	Liquid	Liquid		
Color	Transparent	Transparent		
Viscosity@25ºC	600-800 cps	50-150 cps		
Density, g/cm3	1.07±0.05	0.95±0.03		
Mix Ratio	1:1 by weight			
Hardness	Shore, D75-80			
Pot Life	40-50mins@25°C			
Curing Time	6-8hrs@35ºC, 10-15hrs@25ºC			
ouning fillio	24hrs, Dry Completely			
Recoat Time	2 Hrs			
Thickness	1-3 mm			
Shelf Life	12 Months			
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.			





No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China