

Non-Yellowing Industrial Epoxy Floor Coating Excellent Adhesion To **Concrete Substrates**

Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-SL5001 • Minimum Order Quantity: 500KG

• Price: US\$2.5-3.8/Kg · Packaging Details: Bottle/Carton/Pallet • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



Product Specification

Shelf Life:

. Labeling Marker: Industrial Strength Epoxy Exceptional Attribute: High Gloss Retention

Key Words: Seamless, High Gloss Finish Epoxy Resin And Hardener Materials: · Application: Wood, Tile, Concrete Mixing Ratio: 5:1 By Weight Pot Life: 30 Minutes

12 Months • Highlight: Non-Yellowing Industrial Epoxy Floor Coating,

Excellent Adhesion Industrial Epoxy Floor

Coating

Concrete Substrates Industrial Epoxy Floor

Coating



Product Description

Non-Yellowing Industrial Epoxy Floor Coating Excellent Adhesion To Concrete Substrates

Quick Details Of Industrial Epoxy Floor Coating:

Industrial epoxy floor coatings are designed to offer slip resistance, often achieved through the inclusion of materials such as quartz, aluminum oxide, or specialty aggregates. These additives create a textured surface that enhances traction, reducing the likelihood of slips, particularly in wet environments. Ensuring proper installation and regular maintenance is key to preserving the slip-resistant qualities of epoxy coatings. For tailored solutions, consulting with experienced epoxy flooring professionals can help in selecting the most suitable products and application techniques for specific requirements.

Features Of Industrial Epoxy Floor Coating:

- 1. Excellent adhesion to concrete substrates
- 2. Can be applied with various thicknesses
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Industrial Epoxy Floor Coating:

Industrial Epoxy floor coating is a flooring system composed of epoxy resin and hardener that creates a strong, durable, and long-lasting surface. Resistant to abrasion, chemicals, and moisture, it's perfect for high-traffic areas in commercial, industrial, and residential spaces. Customizable in colors and patterns for a decorative touch, it's easy to maintain without harsh chemicals. Slip-resistant for safety, it suits various substrates like concrete, wood, and metal, offering versatility. With its durability, customization options, and low-maintenance properties, epoxy floor coating is a popular and practical choice for both residential and commercial applications.

Product Descriptions Of Industrial Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China