

Textured Coatings Non Slip Epoxy Floor Coating Offer Non-Slip Surfaces For Safety

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Shelf Life:

Brand Title: Garage Floor FinishMark: Quick Curing Time

Key Words: Seamless, High Gloss Finish
Materials: Epoxy Resin And Hardener
Application: Wood, Tile, Concrete
Mixing Ratio: 3:1 By Weight
Pot Life: 40 Minutes

• Highlight: Safety Epoxy Floor Coating,

12 Months

Non Slip Epoxy Floor Coating,

Textured Coatings Epoxy Floor Coating



Product Description

Textured Coatings Non Slip Epoxy Floor Coating Offer Non-Slip Surfaces For Safety

Quick Details Of Non Slip Epoxy Floor Coating:

When embarking on the application of Non-Slip Epoxy Floor Coating, meticulous surface preparations are vital. Prioritizing thorough cleaning to eliminate any debris, oils, or contaminants is key. Additionally, addressing any imperfections like cracks, holes, or uneven surfaces is crucial to ensure a seamless foundation for the epoxy coating. Employing specialized surface profiling techniques such as diamond grinding or shot blasting can further enhance adhesion and optimize the non-slip properties of the coating. Following precise manufacturer guidelines and confirming that the surface is impeccably clean, structurally sound, and adequately prepared are pivotal steps in achieving a durable and safe non-slip epoxy flooring system.

Features Of Non Slip Epoxy Floor Coating:

- 1. Moisture-tolerant epoxies work in damp areas
- 2. Textured coatings offer non-slip surfaces for safety
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China