

# Chemical-Resistant Non Slip Epoxy Floor Coating Fast-Set Formulations Allow Same-Day Use

## **Basic Information**

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

• Supply Ability: 1000 Ton/Month



# **Product Specification**

Merchandise Tag: Garage Epoxy Coating
 Trait: Non-Toxic Formulation
 Key Words: Seamless, High Gloss Finish
 Materials: Epoxy Resin And Hardener
 Application: Wood, Tile, Concrete

Mixing Ratio: 3:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

Highlight: Chemical-Resistant Epoxy Floor Coating,

**Epoxy Floor Coating Non-Toxic** 



## **Product Description**

#### Chemical-Resistant Non Slip Epoxy Floor Coating Fast-Set Formulations Allow Same-Day Use

#### **Quick Details Of Non Slip Epoxy Floor Coating:**

When preparing for the application of Non-Slip Epoxy Floor Coating, meticulous surface preparation is paramount. Thoroughly cleaning the surface to eliminate dirt, oils, and contaminants is essential. Additionally, addressing any cracks, holes, or uneven areas in the substrate is crucial to ensure a seamless base for the epoxy application. Utilizing specialized surface profiling techniques such as diamond grinding or shot blasting can further improve adhesion and enhance the non-slip properties of the coating. Following precise manufacturer guidelines and ensuring that the surface is immaculately clean, structurally sound, and properly primed are critical steps in achieving a durable and safe non-slip epoxy flooring system.

#### Features Of Non Slip Epoxy Floor Coating:

- 1. Provide visibility in low-light environments
- 2. Suitable for areas exposed to harsh substances
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

#### **Advantages Of Non Slip Epoxy Floor Coating:**

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

#### **Product Descriptions Of Non Slip Epoxy Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China