

High-Gloss Non Slip Epoxy Floor Coating Creates Mirror-Like Finish

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Line Identifier: Best Epoxy Floor Coating
Peculiarity: Self-Leveling Properties
Key Words: Seamless, High Gloss Finish
Materials: Epoxy Resin And Hardener
Application: Wood, Tile, Concrete
Mixing Ratio: 3:1 By Weight

Pot Life: 40 MinutesShelf Life: 12 Months

Highlight: Mirror-Like Finish Epoxy Floor Coating,
 High-Gloss Non Slip Epoxy Floor Coating



Product Description

High-Gloss Non Slip Epoxy Floor Coating Creates A Mirror-Like Finish

Quick Details Of Non Slip Epoxy Floor Coating:

When preparing to apply Non-Slip Epoxy Floor Coating, meticulous surface priming is key. Thoroughly cleansing the area to eliminate debris, oils, and contaminants is essential. Additionally, addressing any cracks, holes, or uneven sections in the substrate is vital to establish a smooth surface for the epoxy application. Utilizing specialized surface profiling techniques like diamond grinding or shot blasting can further enhance adhesion and optimize the anti-slip features of the coating. Adhering closely to manufacturer guidelines and ensuring the surface is flawlessly clean, structurally sound, and adequately primed are crucial steps in achieving a durable and secure non-slip epoxy flooring system.

Features Of Non Slip Epoxy Floor Coating:

- 1. Make cleaning vandalism easier and quicker
- 2. Creates a mirror-like finish for a sleek appearance
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	







(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China