

Conductive Epoxy Flooring Non Slip Epoxy Floor Coating Dissipates Static Electricity

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

• Stock Label: Industrial Epoxy

Element: Water-Clear Transparency
Key Words: Seamless, High Gloss Finish
Materials: Epoxy Resin And Hardener
Application: Wood, Tile, Concrete
Mixing Ratio: 3:1 By Weight
Pot Life: 40 Minutes

• Shelf Life: 12 Months

Highlight: Dissipates Static Electricity Epoxy Floor

Coating

, Non Slip Epoxy Floor Coating, Conductive Epoxy Floor Coating



Product Description

Conductive Epoxy Flooring Non Slip Epoxy Floor Coating Dissipates Static Electricity

Quick Details Of Non Slip Epoxy Floor Coating:

In the meticulous process of preparing for the Non-Slip Epoxy Floor Coating application, comprehensive surface priming is of utmost importance. Thoroughly removing any dirt, oils, residues, and impurities from the surface is critical. Moreover, addressing any surface irregularities such as divots, seams, or bumps is essential to ensure a level foundation for the epoxy coat. Employing advanced surface preparation techniques like scarification or diamond honing can significantly boost adhesion and optimize the slip-resistant features of the coating. Adhering precisely to the manufacturer's instructions and guaranteeing that the surface is flawlessly clean, structurally robust, and adequately primed are key steps in achieving a durable and secure non-slip epoxy flooring system.

Features Of Non Slip Epoxy Floor Coating:

- 1. Withstands extreme heat without degrading
- 2. Ideal for areas with heavy machinery and traffic
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China