

Epoxy Primers Non Slip Epoxy Floor Coating Enhance Adhesion And Durability Of Topcoats

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Product Tagline: Epoxy Over Concrete
 Distinctive Quality: Resistance For Durability
 Key Words: Seamless, High Gloss Finish
 Materials: Epoxy Resin And Hardener
 Application: Wood, Tile, Concrete

Mixing Ratio: 3:1 By WeightPot Life: 40 MinutesShelf Life: 12 Months

• Highlight: Enhance Adhesion Epoxy Floor Coating,

 ${\bf Enhance\ Durability\ Epoxy\ Floor\ Coating},$

Non Slip Epoxy Floor Coating



Product Description

Epoxy Primers Non Slip Epoxy Floor Coating Enhance Adhesion And Durability Of Topcoats

Quick Details Of Non Slip Epoxy Floor Coating:

In the meticulous preparation for applying Non-Slip Epoxy Floor Coating, surface priming takes precedence. Thoroughly cleansing the substrate to eliminate dirt, oils, grease, and contaminants is imperative. Furthermore, rectifying any imperfections like cracks, spalls, or irregularities in the surface is essential to establish a flawless canvas for the epoxy application. Employing advanced surface preparation techniques such as scarifying or acid etching can significantly improve bonding and enhance the anti-slip characteristics of the coating. Adhering rigorously to manufacturer specifications and ensuring that the surface is immaculately clean, structurally sound, and appropriately primed are pivotal steps in creating a durable and secure non-slip epoxy flooring solution.

Features Of Non Slip Epoxy Floor Coating:

- 1. Fast-set epoxy allows for quick installation
- 2. Enhance adhesion and durability of topcoats
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China