Basic Information

. Place of Origin: **CHINA** Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-WZ3001 • Minimum Order Quantity: 500KG

• Price: US\$2.5-3.8/Kg Bottle/Carton/Pallet · Packaging Details: • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



Product Specification

. Commodity Name: Poured Epoxy Floor

. Special Trait: Non-Yellowing Over Time . Key Words: Seamless, High Gloss Finish Epoxy Resin And Hardener Materials: Wood, Tile, Concrete · Application:

Mixing Ratio: 3:1 By Weight Pot Life: 40 Minutes Shelf Life: 12 Months

• Highlight: Best Epoxy Floor Coating,

Sunlight Exposure Epoxy Sealers,

UV-Stable Epoxy Sealers



Our Product Introduction

Product Description

UV-Stable Epoxy Sealers Best Epoxy Floor Coating Resists Sunlight Exposure

Quick Details Of Non Slip Epoxy Floor Coating:

Exploring the world of Non-Slip Epoxy Floor Coating reveals a diverse array of color and decorative options, each crafted to cater to distinct tastes and functional requirements. Choices include solid colors for a traditional look, flakes for added texture and slip resistance, metallic epoxy for a contemporary sheen, quartz for lasting durability, custom designs for personalization or branding, and color blends for a unique aesthetic appeal. Opting for the perfect color and decorative scheme involves considering factors such as the intended use of the space, design preferences, durability needs, and maintenance considerations. Seeking guidance from experts can aid in making informed decisions to create a Non-Slip Epoxy Floor Coating that not only visually captivates but also aligns perfectly with the specific demands of the setting.

Features Of Non Slip Epoxy Floor Coating:

- 1. Resists degradation from sunlight exposure
- 2. Offer a seamless and durable finish
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China