



Self-Leveling Industrial Epoxy Floor Coating Ensures A Flat And Smooth Surface Effortlessly

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Place of Origin: CHINA
- Brand Name: CREKOAT
- Certification: TDS, MSDS
- Model Number: CK-WZ3001
- Minimum Order Quantity: 500KG
- Price: US\$2.5-3.8/Kg
- Packaging Details: Bottle/Carton/Pallet
- Delivery Time: 3-7 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Ton/Month



Product Specification

- Labeling Title: Commercial Kitchen Floor Paint
- Exceptional Facet: Food-Safe Certification
- Key Words: Seamless, High Gloss Finish
- Materials: Epoxy Resin And Hardener
- Application: Wood, Tile, Concrete
- Mixing Ratio: 3:1 By Weight
- Pot Life: 40 Minutes
- Shelf Life: 12 Months
- Highlight: Industrial Epoxy Floor Coating,
Self-Leveling Epoxy Floor Coating,
Smooth Surface Epoxy Floor Coating



Product Description

Self-Leveling Industrial Epoxy Ensures A Flat And Smooth Surface Effortlessly

Quick Details Of Non Slip Epoxy Floor Coating:

Venturing into the world of Non-Slip Epoxy Floor Coating unveils a rich tapestry of color and decorative choices. From timeless solid shades to textured flakes, sleek metallic finishes, and resilient quartz-infused coatings, the possibilities are diverse. Personalized designs cater to unique branding or individual style, while custom color blends offer a bespoke aesthetic. Careful consideration of space functionality, design preferences, and maintenance requirements, coupled with expert advice, guarantees a visually striking and practical flooring solution.

Features Of Non Slip Epoxy Floor Coating:

1. Ensures a flat and smooth surface effortlessly
2. Marbling techniques produce elegant designs
3. Waterproofing capabilities barrier finish
4. Easy to apply, easy clean and maintain
5. Withstand heavy equipment and machinery
6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

| Item | Epoxy Resin(A) | Hardener(B) |
|--------------|---|-------------|
| Appearance | Liquid | Liquid |
| Color | Custom Colors | Transparent |
| Density@25°C | 1.3g/cm3 | |
| Mix Ratio | 3:1 by weight | |
| Hardness | 3H | |
| Pot Life | 30-40mins@25°C | |
| Curing Time | 12-15hrs@35°C, 16-24hrs@25°C 24hrs, Dry Completely | |
| Recoat Time | 2 Hrs | |
| Thickness | 1-3 mm | |
| Shelf Life | 12 Months | |
| Application | Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms. | |





+8615017402317



info@crecoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China