

Quartz Epoxy Floor Finish Durable And Low-Maintenance Solution

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-WZ3001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Ware Nomenclature: Flexible Epoxy For Wood Floors

• Rare Distinction: Flexible Formulation

Key Words: Seamless, High Gloss Finish
Materials: Epoxy Resin And Hardener
Application: Wood, Tile, Concrete
Mixing Ratio: 3:1 By Weight

Mixing Ratio: 3:1 By Well
Pot Life: 40 Minutes
Shelf Life: 12 Months

• Highlight: Durable Quartz Epoxy Floor Finish,

Low-Maintenance Quartz Epoxy Floor Finish



Product Description

Quartz Epoxy Floor Finish Offers A Durable And Low-Maintenance Solution

Quick Details Of Non Slip Epoxy Floor Coating:

Exploring the realm of Non-Slip Epoxy Floor Coating reveals a myriad of color and decorative options tailored to individual tastes. From classic solid colors to textured flakes, modern metallic finishes, and durable quartz coatings, the choices are extensive. Custom designs allow for personalization and branding, while color blends offer a unique aesthetic appeal. Selecting the ideal color scheme involves considering factors like space usage, design preferences, durability needs, and maintenance requirements. Collaboration with experienced professionals ensures a well-informed decision, creating a visually appealing and functional Non-Slip Epoxy Floor Coating that suits the specific demands of the space.

Features Of Non Slip Epoxy Floor Coating:

- 1. Controls static electricity in sensitive environments
- 2. Offers a durable and low-maintenance solution
- 3. Waterproofing capabilities barrier finish
- 4. Easy to apply, easy clean and maintain
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Non Slip Epoxy Floor Coating:

Non-slip epoxy floor coatings provide a comprehensive solution by effectively merging safety, durability, and aesthetic appeal. Designed to enhance traction and reduce the risk of slips in high-traffic areas, these coatings are particularly suited for industrial settings. Their resilience against heavy foot traffic and impacts, combined with exceptional chemical resistance, makes them an excellent choice for demanding environments. Easy to maintain and available in various colors and finishes, non-slip epoxy coatings not only prioritize safety and longevity but also elevate the visual appeal of the space, catering to diverse needs across industrial, commercial, and residential settings.

Product Descriptions Of Non Slip Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	3:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2 Hrs	
Thickness	1-3 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China