

Epoxy Flake Floor Coating For Residential Commercial And Industrial Spaces

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-TC2001
Minimum Order Quantity: 500KG

Price: US\$3.2-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Product Designation: Green Epoxy Flakes Aspects: Versatile Applications

Key Words: Fast Curing

Materials: 100% Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 2:1 By Weight
Pot Life: 30 Minutes
Shelf Life: 12 Months

• Highlight: Commercial Epoxy Flake Floor Coating,

Industrial Epoxy Flake Floor Coating, Residential Epoxy Flake Floor Coating



Product Description

Epoxy Flake Floor Coating For Residential Commercial And Industrial Spaces

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings excel in both residential and commercial spaces, offering unmatched durability and customizable aesthetics. Ideal for garages, kitchens, retail stores, and industrial facilities, they resist stains, impacts, and heavy traffic. Their standout feature is the ability to incorporate UV-resistant, antimicrobial, or eco-friendly formulations, enhancing longevity and sustainability. With decorative flakes in endless colors and textures, they create unique, slip-resistant finishes. Professionally installed, they deliver a seamless, long-lasting surface that combines practicality with stunning visual appeal, making them a top choice for innovative, high-performance flooring.

Features Of Epoxy Flake Floor Coating:

- 1. Provides a durable finish that lasts for years
- 2. Suitable for residential, commercial, and industrial spaces
- 3. Enhances safety with slip-resistant properties
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa⋅s	300-500 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25°C	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial	
	Use - Shopping malls and boutiques, Hotels, Offices, Showrooms,	
	Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use -	
	Entrances and hallways, basements, entertainment rooms, bathrooms,	
	kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China