

Texture Epoxy Flake Floor Coating In Varying Thicknesses For Different Needs

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-TC2001
Minimum Order Quantity: 500KG

Price: US\$3.2-4.5/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Product Signature: Full Flake Garage Floor
 Specifications: Scratch Resistant
 Key Words: Fast Curing

Materials: 100% Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 2:1 By Weight

Pot Life: 30 MinutesShelf Life: 12 Months

• Highlight: Texture Epoxy Flake Floor Coating,

Varying Thicknesses Epoxy Flake Floor Coating , Fast Curing Epoxy Flake Floor Coating



Product Description

Texture Epoxy Flake Floor Coating In Varying Thicknesses For Different Needs

Quick Details Of Epoxy Flake Floor Coating:

Epoxy flake floor coatings elevate spaces with their unique blend of durability, customization, and advanced technology. Perfect for homes, retail stores, and industrial facilities, they resist stains, impacts, and heavy traffic while offering a sleek, easy-to-clean surface. Their standout feature is the integration of UV-resistant, antimicrobial, or eco-friendly options, enhancing longevity and sustainability. With decorative flakes available in endless colors and textures, they create personalized, slip-resistant designs tailored to any aesthetic. Professionally installed, epoxy flake floors provide a seamless, durable, and visually stunning finish, making them the ultimate choice for spaces that demand both high performance and innovative style.

Features Of Epoxy Flake Floor Coating:

- 1. Adds depth and texture to the flooring design
- 2. Can be applied in varying thicknesses for different needs
- 3. Enhances safety with slip-resistant properties
- 4. Easy to apply, clean and maintain
- 5. Naturally de-foaming with no ripples
- 6. Durable, high gloss, water resistant

Advantages Of Epoxy Flake Floor Coating:

Epoxy flake floor coating is a highly-durable floor coating application that incorporates a double broadcast of colored flakes chips with epoxy resin and polyaspartic coatings. The system provides flooring solutions for the most demanding heavy-traffic environments, specifically in areas that require significant traction. The durable and stunning appearance that comes from this epoxy finish will endure for many years to come, with minimal or no maintenance other than regular cleaning using mild cleaning products. UV stable epoxy flake coating offers seamless, safe, highly durable, and easy to clean solutions to meet the most demanding flooring challenges.

Product Descriptions Of Epoxy Flake Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Viscosity@25°C	700-900 mPa⋅s	300-500 mPa⋅s
Density, g/cm3	1.07±0.05	0.95±0.03
Mix Ratio	2:1 by weight	
Hardness	Shore, D80-85	
Pot Life	30-40mins@25ºC	
Curing Time	6-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5 mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China