

Standard Topcoat Industrial Epoxy Floor Coating With Fast Curing **Times**

Basic Information

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** · Certification: TDS, MSDS Model Number: CK-PT4001 • Minimum Order Quantity: 500KG • Price: US\$2.5-3.8/Kg

· Packaging Details: Bottle/Carton/Pallet • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



Product Specification

Shelf Life:

• Product Line: White Epoxy Floor Distinctions: Impact Resistant . Key Words: **Durable Surface** Materials: High Solids Epoxy Wood, Tile, Concrete · Application: Mixing Ratio: 4:1 By Weight Pot Life: 30 Minutes

12 Months • Highlight: Standard Topcoat Industrial Epoxy Floor

, Industrial Epoxy Floor Coating

CREKOAT

Product Description

Standard Topcoat Industrial Epoxy Floor Coating With Fast Curing Times

Quick Details Of Industrial Epoxy Floor Coating:

Industrial epoxy floor coatings provide durable, chemical-resistant surfaces ideal for demanding environments. These seamless systems offer excellent adhesion to concrete, withstanding heavy traffic, impacts, and frequent cleaning. Available in various finishes (glossy, matte, or textured for slip resistance), they create hygienic, easy-to-maintain floors for factories, warehouses, and food processing plants. The coatings resist oils, solvents, and mild acids while providing long-lasting protection. With fast curing times and customizable colors, epoxy floors combine functionality with aesthetic appeal for industrial and commercial applications.

Features Of Industrial Epoxy Floor Coating:

- 1. Thermal shock resistant (-40°C to 120°C) for cold storage applications
- 2. Self-healing properties for minor scratch resistance
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Industrial Epoxy Floor Coating:

Industrial epoxy floor coatings offer exceptional durability, chemical resistance, and long-term cost savings, making them ideal for high-traffic facilities. Their seamless, non-porous surface resists oils, acids, and abrasions while ensuring easy cleaning and maintenance. With high adhesion strength and customizable finishes (anti-slip, UV-resistant, or decorative), they enhance safety and aesthetics. Epoxy floors also feature fast curing times, minimizing downtime, and can withstand heavy loads, making them perfect for factories, warehouses, and garages. Low-VOC options provide eco-friendly solutions without compromising performance.

Product Descriptions Of Industrial Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12 M	lonths
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China