

# **Standard Epoxy Floor Coating Can Incorporate Anti-Slip Aggregates**

### **Basic Information**

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-PT4001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



## **Product Specification**

Shelf Life:

Product Range: 2 Pack Epoxy Floor Paint

Determinants: Stain Proof
Key Words: Durable Surface
Materials: High Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 4:1 By Weight
Pot Life: 30 Minutes

Highlight: Anti-Slip Epoxy Floor Coating,
 Standard Epoxy Floor Coating

12 Months



### **Product Description**

#### Standard Epoxy Floor Coating Can Incorporate Anti-Slip Aggregates

#### **Quick Details Of Industrial Epoxy Floor Coating:**

Industrial epoxy floor coatings provide versatile, hardworking surfaces for demanding commercial spaces. These durable floors withstand constant forklift traffic, dropped tools, and chemical spills while maintaining a clean, polished look. The non-porous surface resists oil absorption and stains, making cleanup in auto shops or industrial kitchens a breeze. Available in both slip-resistant textures for safety and glossy finishes for enhanced lighting, they adapt to various business needs. Easy to install over existing concrete with minimal downtime, epoxy floors offer years of reliable service with just routine mopping - an economical solution for warehouses, garages, and production areas where both durability and presentability matter.

#### Features Of Industrial Epoxy Floor Coating:

- 1. Repels common industrial fluids
- 2. Can incorporate anti-slip aggregates
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

#### **Advantages Of Industrial Epoxy Floor Coating:**

Industrial epoxy floor coatings offer exceptional durability, chemical resistance, and long-term cost savings, making them ideal for high-traffic facilities. Their seamless, non-porous surface resists oils, acids, and abrasions while ensuring easy cleaning and maintenance. With high adhesion strength and customizable finishes (anti-slip, UV-resistant, or decorative), they enhance safety and aesthetics. Epoxy floors also feature fast curing times, minimizing downtime, and can withstand heavy loads, making them perfect for factories, warehouses, and garages. Low-VOC options provide eco-friendly solutions without compromising performance.

#### **Product Descriptions Of Industrial Epoxy Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	4:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China