

High Performance Epoxy Middle Coat 100% Solids Self-Leveling Formula

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-MD5001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

Shelf Life:

Product Specification: Warehouse Floor Epoxy
Aspects: Quick Recoat Time
Key Words: Durable Surface
Materials: High Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 5:1 By Weight
Pot Life: 30 Minutes

• Highlight: Solids Epoxy Middle Coat,

12 Months

Self-Leveling Epoxy Middle Coat, High Performance Epoxy Middle Coat



Product Description

High-Performance Epoxy Middle Coat 100% Solids Self-Leveling Formula

Quick Details Of Industrial Epoxy Floor Coating:

This high-performance middle coat features a 100% solids, self-leveling formula that builds thickness (1-3mm per layer) while providing exceptional impact and chemical resistance. Its flexible polymer matrix prevents cracking under thermal stress or heavy loads, and the aggregate-compatible design allows for quartz sand or colored flake blending to enhance slip resistance and aesthetics. With fast recoat times (as little as 4 hours) and excellent intercoat adhesion, it creates a durable, seamless transition between primer and topcoat layers. Ideal for industrial plants, warehouses, and commercial spaces requiring long-lasting protection with minimal maintenance. Available in various colors and textures to match decorative or functional requirements.

Features Of Industrial Epoxy Floor Coating:

- 1. Customizable thickness from 0.5mm to 10mm
- 2. Rapid curing formulas (8-24 hour turnaround)
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Industrial Epoxy Floor Coating:

Industrial epoxy floor coatings offer exceptional durability, chemical resistance, and long-term cost savings, making them ideal for high-traffic facilities. Their seamless, non-porous surface resists oils, acids, and abrasions while ensuring easy cleaning and maintenance. With high adhesion strength and customizable finishes (anti-slip, UV-resistant, or decorative), they enhance safety and aesthetics. Epoxy floors also feature fast curing times, minimizing downtime, and can withstand heavy loads, making them perfect for factories, warehouses, and garages. Low-VOC options provide eco-friendly solutions without compromising performance.

Product Descriptions Of Industrial Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	4-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China