

# Standard Epoxy Mid-Coats Offering Industrial-Grade Protection And **Aesthetic**

### **Basic Information**

. Place of Origin: **CHINA** . Brand Name: **CREKOAT** TDS, MSDS · Certification: Model Number: CK-MD5001 Minimum Order Quantity: 500KG

• Price: US\$2.5-3.8/Kg Packaging Details: Bottle/Carton/Pallet • Delivery Time: 3-7 Working Days

Payment Terms: T/T

. Supply Ability: 1000 Ton/Month



## **Product Specification**

• Product Listing: Best Epoxy Floor Paint Factors: Anti-Microbial Additives **Durable Surface** . Key Words: Materials: High Solids Epoxy Wood, Tile, Concrete · Application: Mixing Ratio: 5:1 By Weight

Pot Life: 30 Minutes . Shelf Life: 12 Months



### **Product Description**

#### Standard Epoxy Mid-Coats Offering Industrial-Grade Protection And Aesthetic

#### **Quick Details Of Industrial Epoxy Floor Coating:**

Engineered to outperform standard epoxy mid-coats, our advanced formula combines superior self-leveling properties with enhanced structural flexibility for unmatched durability. The unique polymer composition not only resists heavy impacts and harsh chemicals but also adapts seamlessly to temperature fluctuations, preventing cracks and delamination. Its innovative texture-blending capability allows for customized slip resistance without sacrificing smoothness, while the extended working time ensures effortless application across large surfaces. Designed for demanding environments, it forms a perfect bond between base and top layers, offering both industrial-grade protection and aesthetic versatility. Ideal for facilities where reliability and seamless performance are critical.

#### Features Of Industrial Epoxy Floor Coating:

- 1. Slip-resistant textures meeting OSHA standards
- 2. Heavy-duty load capacity (up to 10,000 psi)
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

#### **Advantages Of Industrial Epoxy Floor Coating:**

Industrial epoxy floor coatings offer exceptional durability, chemical resistance, and long-term cost savings, making them ideal for high-traffic facilities. Their seamless, non-porous surface resists oils, acids, and abrasions while ensuring easy cleaning and maintenance. With high adhesion strength and customizable finishes (anti-slip, UV-resistant, or decorative), they enhance safety and aesthetics. Epoxy floors also feature fast curing times, minimizing downtime, and can withstand heavy loads, making them perfect for factories, warehouses, and garages. Low-VOC options provide eco-friendly solutions without compromising performance.

#### **Product Descriptions Of Industrial Epoxy Floor Coating:**

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	4-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









( +8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China