

Anti Static Epoxy Mid-Coat Self-Leveling Properties For A Flawless Finish

Basic Information

Place of Origin: CHINA
Brand Name: CREKOAT
Certification: TDS, MSDS
Model Number: CK-MD5001
Minimum Order Quantity: 500KG

Price: US\$2.5-3.8/Kg
 Packaging Details: Bottle/Carton/Pallet
 Delivery Time: 3-7 Working Days

Payment Terms: T/T

Supply Ability: 1000 Ton/Month



Product Specification

. Shelf Life:

Product Series: Industrial Epoxy Paint Characteristics: Eco-Conscious Flooring

Key Words: Durable Surface
Materials: High Solids Epoxy
Application: Wood, Tile, Concrete
Mixing Ratio: 5:1 By Weight
Pot Life: 30 Minutes

12 Months

CREKOAT



Product Description

Anti Static Epoxy Mid-Coat Self-Leveling Properties For A Flawless Finish

Quick Details Of Industrial Epoxy Floor Coating:

Our epoxy middle coat redefines flooring performance with its adaptive polymer technology that actively compensates for substrate movement while maintaining exceptional load-bearing capacity. The self-regulating viscosity ensures perfect self-leveling properties for a flawless finish, even on uneven surfaces. Unlike conventional middle coats, our formula creates a chemical fusion with both primer and topcoat layers, forming an unbreakable bond that resists delamination. The unique micro-textured surface provides ideal mechanical adhesion for topcoats while offering built-in stress relief to prevent cracking. Designed for high-traffic industrial and commercial applications, it delivers the perfect balance between rugged durability and refined aesthetics, serving as the critical performance layer in any premium flooring system.

Features Of Industrial Epoxy Floor Coating:

- 1. Decorative flake and quartz options
- 2. Conductive versions for static control
- 3. Non-slip surface for enhanced safety
- 4. Easy to apply, clean and maintain surface
- 5. Withstand heavy equipment and machinery
- 6. Suitable for industries and commercial spaces

Advantages Of Industrial Epoxy Floor Coating:

Industrial epoxy floor coatings offer exceptional durability, chemical resistance, and long-term cost savings, making them ideal for high-traffic facilities. Their seamless, non-porous surface resists oils, acids, and abrasions while ensuring easy cleaning and maintenance. With high adhesion strength and customizable finishes (anti-slip, UV-resistant, or decorative), they enhance safety and aesthetics. Epoxy floors also feature fast curing times, minimizing downtime, and can withstand heavy loads, making them perfect for factories, warehouses, and garages. Low-VOC options provide eco-friendly solutions without compromising performance.

Product Descriptions Of Industrial Epoxy Floor Coating:

Item	Epoxy Resin(A)	Hardener(B)
Appearance	Liquid	Liquid
Color	Transparent	Transparent
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	4-8hrs@35°C, 10-15hrs@25°C	
	24hrs, Dry Completely	
Recoat Time	2Hrs	
Thickness	1-5mm	
Shelf Life	12 Months	
Application	Industrial Use - Garages, Warehouses, Airports and hangars. Commercial Use - Shopping malls and boutiques, Hotels, Offices, Showrooms, Restaurants, Hospitals, Schools, Bar Tops, Table Tops. Residential Use - Entrances and hallways, basements, entertainment rooms, bathrooms, kitchens and living rooms.	









(+8615017402317 info@crekoat.com epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China