

Anti-Slip Waterproof Epoxy Floor Coating with Customizable Color for Industrial Concrete Sealer


Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Certification: ISO14001, CCC, RoHS, ISO9001
- Minimum Order Quantity: 100
- Price: 3.5


CREKOAT



Product Specification

- Color: Customized
- Appearance: Liquid
- Main Material: Epoxy
- Mix Ratio: 5:1 By Weight
- Shelf Life: 12 Months
- Finish Type: High Gloss
- Packaging Size: 20Kg/Bucket
- Density: 1.3g/cm3
- Hardness: 3H
- Pot Life: 30-40mins@25°C
- Curing Time: 8-10hrs@35°C, 15-20hrs@25°C
- Recoat Time: 2Hrs
- Thickness: 1-3mm
- Drying Method: Air Drying
- Production Capacity: 1000000t/Year

CREKOAT




More Images


CREKOAT




CREKOAT



CREKOAT



CREKOAT



Product Description

Anti-Slip Waterproof Polyurea Concrete Joint Filler Concrete Sealer

Epoxy Floor Coatings provide a fast-drying, tough, and protective coating for concrete, metals and other materials, offering resistance to chemicals such as acids. This makes epoxy suitable as a coating for floors exposed to medium and heavy loads in storage areas, warehouses and production facilities. When used in flooring applications, epoxy coatings result in durable, long-lasting solutions with decorative, high-gloss finishes available in various colors.

Key Features

- Seamless, high gloss finish
- Resistant to stains and water
- Durable, tough, and strong construction
- Fast application with 24-hour cure time
- Easy to clean and maintenance free
- Withstands heavy use and mechanical loads

Product Advantages

Epoxy flooring is ideal for environments requiring resistance to extreme temperatures, foot and machine traffic, chemicals, oil, and other fluids without peeling or corrosion. Its seamless poured application eliminates joints, ridges, and crevices where dirt and bacteria can accumulate, making it a sanitary choice for food processing, pharmaceutical, industrial, and manufacturing facilities. The smooth surface allows easy movement of equipment like hospital gurneys or forklifts.

Technical Specifications

Item	Epoxy Resin(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Clear
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C (24hrs for complete drying)	
Recoat Time	2Hrs	
Thickness	1-3mm	
Shelf Life	12 Months	

Applications

Epoxy coatings are typically applied over concrete floors to create high-performance, smooth, and durable surfaces that withstand years of heavy use. Industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean, safe conditions for workers, equipment, and inventory.



Company Profile

Established in 1993, Guangdong Crecoat New Materials Co., Ltd. was formed by epoxy resin industry experts to meet growing demand for high-quality resin products. With two factories in Foshan and Dongguan covering 20,000m² and annual output of 1,000,000 tons, we've become one of China's leading epoxy resin suppliers. Our facilities feature advanced production equipment, precise testing instruments, and strict quality assurance systems certified to ISO9001 and ISO14001 standards. With over 20 years of experience, our products have

passed SGS and RoHS environmental inspections.

Frequently Asked Questions

Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

Q5: How many days will you deliver the products?

A5: Generally it will take 3-7 days to produce the products.

Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

Building C, Tang's Industrial Zone, Gaopu Town, Dongguan City, China