

5:1 Mix Ratio 20Kg/Bucket Epoxy Floor Coating with 12 Months Shelf Life Industrial Epoxy Coating

Basic Information

• Certification: ISO14001, CCC, RoHS, ISO9001

Minimum Order Quantity: 100Price: 3.5



Product Specification

201-176-9 . EINECS Number: · Color: Customized Appearance: Liquid . Main Material: Ероху · Application Method: Roller • Drying Method: Air Drying Substrate: Cement Base 5:1 By Weight Mix Ratio: . Shelf Life: 12 Months • Finish Type: High Gloss • Package Specification: 20Kg/Bucket

• Pot Life: 30-40mins@25°C

• Curing Time: 8-10hrs@35°C, 15-20hrs@25°C

ЗН

1.3g/cm3



More Images

Density:Hardness:









Product Description

Chemical Resistant Industrial Factory Warehouse Coating Epoxy Resin for Floor

Industrial Epoxy Floor Coating offers durable, self-leveling or trowel-applied solutions (1-5mm thickness) with 0.3-1.5kg/m² coverage per mm. Featuring rapid curing (walkable in 12-24hrs), exceptional chemical/abrasion resistance, and seamless finish, it's ideal for warehouses, factories, and food plants. Available in standard or custom RAL colors, packaged in 25kg resin pails + 5kg hardener cans (12 months shelf life). Includes anti-slip options and free technical support.

Product Features

High-Performance Protection:

Our industrial epoxy floor coating provides superior resistance to chemicals, abrasion, and heavy traffic, ensuring long-lasting durability.

Seamless & Hygienic:

The self-leveling formula creates a smooth, non-porous surface that is easy to clean and ideal for sterile environments.

Fast Curing & Versatile:

Walkable within 12-24 hours and fully cured in 7 days, suitable for warehouses, factories, and food processing plants.

Customizable Solutions:

Available in standard colors or custom RAL matches, with optional anti-slip additives for enhanced safety.

Heavy-Duty Load Bearing:

Withstands extreme mechanical stress and impact from forklifts, pallet jacks, and heavy machinery without cracking or peeling.

Superior Adhesion:

Bonds strongly to concrete, metal, and other substrates, preventing delamination even under heavy use.

Technical Specifications

Item	Epoxy Base Material(A)	Epoxy Hardener(B)	
Appearance	Liquid	Liquid	
Color	Custom Colors	Clear	
Density@25ºC	1.3g/cm3		
Mix Ratio	5:1 by weight		
Hardness	3Н		
Pot Life	30-40mins@25°C		
Curing Time	8-10hrs@35°C, 15-20hrs@25°C		
Recoat Time	2Hrs		
Thickness	1-3mm		
Shelf Life	12 Months		

Epoxy coatings are normally applied over concrete floors to provide a high-performance, smooth, and durable surface that can last many years and withstand heavy loads. Many industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean and safe conditions for workers, equipment, and inventory.

Company Profile

Guangdong Crekoat New Materials Co., Ltd. is a leading manufacturer and supplier of high-quality coatings, specializing in epoxy resin and epoxy floor coatings. Our products are designed to provide durable and attractive surfaces for various applications, including commercial, industrial, and residential settings.

Our epoxy resin products are formulated to provide superior performance, reliability, and versatility. We offer a range of epoxy resins, including standard and specialty resins, that can be used for coatings, adhesives, and other applications. Our experienced team can provide customized solutions to meet the specific requirements of each customer.

Our epoxy floor coatings are designed to provide a durable, attractive, and easy-to-maintain surface for a variety of applications. We offer a range of epoxy floor coatings, including self-leveling, non-slip, and decorative coatings, to meet any need. Our coatings are formulated to provide excellent adhesion, impact resistance, and chemical resistance.

At Guangdong Crekoat New Materials Co., Ltd., we are committed to providing our customers with eco-friendly and innovative coating solutions that meet their unique needs. We use advanced technology and work with a team of experienced professionals to provide customized coating solutions that exceed our customers' expectations. Contact us today to learn more about our products and services and how we can help meet your coating needs.

Our Vision: Become an industry-leading and competitive flooring solution service provider.

Our Mission: Lead a green and environment-friendly flooring global trend.

Frequently Asked Questions

Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

Q5: How many days will you delivery the products?

A5: Generally it will take 3-7 days to produce the products.

Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.





+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China