

Industrial Epoxy Floor Coating Self Leveling Epoxy Flooring with 5:1 Mix Ratio 12 Months Shelf Life 20Kg/Bucket

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Certification: ISO14001, CCC, RoHS, ISO9001
- Minimum Order Quantity: 100
- Price: 3.3




Product Specification

- Color: Customized
- Appearance: Liquid
- Main Material: Epoxy
- Mix Ratio: 5:1 By Weight
- Shelf Life: 12 Months
- Finish Type: High Gloss
- Package Size: 20Kg/Bucket
- Density: 1.3g/cm³
- Hardness: 3H
- Pot Life: 30-40mins@25°C
- Curing Time: 12-15hrs@35°C, 16-24hrs@25°C
- Recoat Time: 2Hrs
- Thickness: 1-3mm
- Coverage: 0.3-1.5kg/m² Per Mm
- Substrate: Cement Base



More Images



Product Description

Industrial Flooring Epoxy Paint Self Leveling Epoxy Flooring for Factory Forklifts

Our industrial epoxy floor coating provides durable, self-leveling or trowel-applied solutions (1-5mm thickness) with 0.3-1.5kg/m² coverage per mm. Featuring rapid curing (walkable in 12-24hrs), exceptional chemical/abrasion resistance, and seamless finish, it's ideal for warehouses, factories, and food plants. Available in standard or custom RAL colors, packaged in 25kg resin pails + 5kg hardener cans (12 months shelf life). Includes anti-slip options and free technical support.

Key Features

High-Performance Protection:

Superior resistance to chemicals, abrasion, and heavy traffic for long-lasting durability.

Seamless & Hygienic:

Self-leveling formula creates smooth, non-porous surface ideal for sterile environments.

Fast Curing & Versatile:

Walkable within 12-24 hours, fully cured in 7 days for warehouses, factories, and food plants.

Customizable Solutions:

Available in standard colors or custom RAL matches with optional anti-slip additives.

Heavy-Duty Load Bearing:

Withstands extreme mechanical stress from forklifts and heavy machinery without cracking.

Superior Adhesion:

Strong bonds to concrete, metal, and other substrates prevent delamination under heavy use.

Technical Specifications

Item	Epoxy Base Material(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Clear
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	12-15hrs@35°C, 16-24hrs@25°C	
Recoat Time	2Hrs	
Thickness	1-3mm	
Shelf Life	12 Months	

Epoxy coatings are normally applied over concrete floors to provide a high-performance, smooth, and durable surface that can last many years and withstand heavy loads. Many industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean and safe conditions for workers, equipment, and inventory.

About Guangdong Crekoat New Materials Co., Ltd.

We are a leading manufacturer and supplier of high-quality coatings, specializing in epoxy resin and epoxy floor coatings. Our products provide durable and attractive surfaces for commercial, industrial, and residential applications.

Our epoxy resin products offer superior performance, reliability, and versatility for coatings, adhesives, and other applications. We provide customized solutions to meet specific customer requirements.

Our epoxy floor coatings create durable, attractive, and easy-to-maintain surfaces with excellent adhesion, impact resistance, and

chemical resistance. We offer self-leveling, non-slip, and decorative coatings.

Committed to eco-friendly and innovative solutions, we use advanced technology and experienced professionals to exceed customer expectations. Contact us to learn how we can meet your coating needs.

Vision: Become an industry-leading and competitive flooring solution service provider.

Mission: Lead a green and environment-friendly flooring global trend.

Frequently Asked Questions

Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

Q5: How many days will you deliver the products?

A5: Generally it will take 3-7 days to produce the products.

Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China