

High Gloss Self Leveling Epoxy Floor Coating with 5:1 Mix Ratio and 12 Months Shelf Life in 20Kg/Bucket

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Certification: ISO14001, CCC, RoHS, ISO9001
- Minimum Order Quantity: 100
- Price: 3.5




Product Specification

- Color: Customized
- Appearance: Liquid
- Main Material: Epoxy
- Mix Ratio: 5:1 By Weight
- Shelf Life: 12 Months
- Finish Type: High Gloss
- Package Specification: 20Kg/Bucket
- Density: 1.3g/cm3
- Hardness: 3H
- Pot Life: 30-40mins@25°C
- Curing Time: 8-10hrs@35°C, 15-20hrs@25°C
- Recoat Time: 2Hrs
- Thickness: 1-3mm
- Drying Method: Air Drying
- Substrate: Cement Base



More Images



Product Description

High Gloss Self Leveling Guangdong Epoxy Floor Coating for Factory Warehouse

Epoxy Floor Coatings are popular because they provide a fast drying, tough, and protective coating for concrete, metals and other materials, which gives resistance to chemicals such as acids. This means epoxy is suitable as a coating on floors that are exposed to medium and heavy loads, for example for storage areas, warehouses and production areas. When used in flooring applications, an epoxy coating will result in a durable, long lasting flooring solution. Epoxy coatings are used over concrete floors in a variety of industries and provide a decorative, high gloss finish that is available in various colours and styles.

Key Features:

- Seamless, high gloss finish
- Resistant to stains and water
- Durable, tough, and strong
- Fast application, cure in 24 hours
- Easy to clean, maintenance free
- Withstands heavy use and mechanical loads

Product Advantages:

Epoxy flooring is the perfect solution for floors that must withstand extreme temperatures, foot and machine traffic, chemicals, oil, and other fluids without peeling or corroding over years of constant use. Food processing, electronics, pharmaceutical, meat and poultry, distilleries, dairy, industrial, and manufacturing facilities are some of the industries for which epoxy flooring is the perfect solution. Because epoxy is poured, there aren't seams, joints, or ridges like with tile or other types of flooring. This makes epoxy a more sanitary flooring option, eliminating cracks and crevices for dirt and bacteria to hide during cleanings. Also, its smooth surface makes it easier for hospital gurneys or forklifts to roll over without jostling or resistance from floor seam bumps.

Technical Specifications:

Item	Epoxy Resin(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Clear
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C	
Dry Completely	24hrs	
Recoat Time	2Hrs	
Thickness	1-3mm	
Shelf Life	12 Months	

Usage:

Epoxy coatings are normally applied over concrete floors to provide a high-performance, smooth, and durable surface that can last many years and withstand heavy loads. Many industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean and safe conditions for workers, equipment, and inventory.



Company Profile

Established in 1993, Guangdong Crecoat New Materials Co., Ltd. was formed by a team of epoxy resin industry experts to meet the growing demand for contractors to buy good quality resin products. Our considerable growth as a company in the last decade has made us one of the leading and most trusted suppliers of epoxy resin products in China.

Guangdong Crecoat New Materials Co., Ltd. has two factories in China, located in Foshan and Dongguan city, covering an area of

20,000m², with an annual output of 1,000,000 tons. Our company has advanced production equipment, precise testing instruments, and strict quality assurance system, passed ISO9001 quality management system and ISO14001 environmental system certification. We have more than 20 years experiences in producing epoxy resin coatings, our products have passed SGS, RoHS environmental protection inspections.



Frequently Asked Questions

Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

Q5: How many days will you delivery the products?

A5: Generally it will take 3-7 days to produce the products.

Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China