# Customizable Color Epoxy Floor Coating with 5:1 Mix Ratio and 12 Months Shelf Life for Industrial Use

# **Basic Information**

• Certification: ISO14001, CCC, RoHS, ISO9001

Minimum Order Quantity: 100Price: 3.5



# **Product Specification**

CK-SL5001 Model NO.: · Color: Customized Liquid Appearance: Main Raw Material: Ероху Roller · Method: Level: Finish Coat • Drying Method: Air Drying Substrate: Cement Base . Components: Pigment

Formation Mechanism: Conversion Type
Mix Ratio: 5:1 By Weight
Shelf Life: 12 Months
Finish Type: High Gloss
Specification: 20Kg/Bucket

• Hardness: 3H



# More Images









### Chemical Resistance Epoxy Resin for Factory Forklifts and Trucks

Epoxy Floor Coatings provide a fast-drying, tough, and protective coating for concrete, metals, and other materials, offering resistance to chemicals such as acids. This makes epoxy suitable for coating floors exposed to medium and heavy loads in storage areas, warehouses, and production facilities. When used in flooring applications, epoxy coatings create durable, long-lasting solutions with decorative, high-gloss finishes available in various colors.

#### **Key Features**

Seamless, high gloss finish

Resistant to stains and water

Durable, tough, and strong

Fast application, cures in 24 hours

Easy to clean, maintenance free

Withstands heavy use and mechanical loads

#### **Product Advantages**

Epoxy flooring is ideal for surfaces that must withstand extreme temperatures, heavy foot and machine traffic, chemicals, oil, and other fluids without peeling or corroding. Its seamless application eliminates joints and ridges, creating a more sanitary surface that's easier to clean and prevents bacteria accumulation. The smooth surface allows for easy movement of hospital gurneys or forklifts without resistance from floor imperfections.

#### **Technical Specifications**

Item	Epoxy Resin(A)	Epoxy Hardener(B)		
Appearance	Liquid	Liquid		
Color	Custom Colors	Clear		
Density@25°C	1.3g/cm3			
Mix Ratio	5:1 by weight			
Hardness	3H			
Pot Life	30-40mins@25°C			
Curing Time	8-10hrs@35°C, 15-20hrs@25°C (24hrs to dry completely)			
Recoat Time	2Hrs			
Thickness	1-3mm			
Shelf Life	12 Months			

# **Applications**

Epoxy coatings are typically applied over concrete floors to create high-performance, smooth, and durable surfaces that can withstand years of heavy use. Industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean, safe conditions for workers, equipment, and inventory.

# **Company Profile**

Established in 1993, Guangdong Crekoat New Materials Co., Ltd. was formed by epoxy resin industry experts to meet growing demand for high-quality resin products. Our significant growth has made us one of China's leading and most trusted epoxy resin suppliers.

With two factories in Foshan and Dongguan covering 20,000m<sup>2</sup> and an annual output of 1,000,000 tons, we feature advanced production equipment, precise testing instruments, and strict quality assurance systems. Our company holds ISO9001 and ISO14001 certifications, with over 20 years of experience producing epoxy resin coatings that meet SGS and RoHS environmental standards.

# **Frequently Asked Questions**

#### Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

# Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

#### Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

#### Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

#### Q5: How many days will you deliver the products?

A5: Generally it will take 3-7 days to produce the products.

#### Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

# Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

#### Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.

# Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China